

# ME1V0U1BABS

## 1. Features

- 28Watts peak pulse power ( $t_p = 8/20\mu s$ )
- Solid-state silicon-avalanche technology
- Capacitance: 0.35pF TYP.
- Low clamping voltage
- Low leakage current
- Complies with following standards:
  - IEC 61000-4-2 (ESD) immunity test Air discharge:  $\pm 18KV$  Contact discharge:  $\pm 16KV$
  - IEC61000-4-4 (EFT) 40A (5/50ns)
  - IEC61000-4-5(Lightning) 7A (8/20us)

## 2. Application

- USB3.0/3.1/ Type-C
- Thunderbolt interface
- DisplayPort interface
- Handheld portable application

## 3. Mechanical Data

- Package: DFN1006
- UL Flammability Classification Rating 94V-0
- Packaging: Tape and Reel
- RoHS/WEEE Compliant

## 4. Absolute Maximum Rating

Parameter	Symbol	Value	Unit
ESD per IEC 61000-4-2 (Contact) ESD per IEC 61000-4-2 (Air)	$V_{ESD}$	$\pm 16$ $\pm 18$	KV
Peak Pulse Power(8/20 $\mu s$ )	$P_{PP}$	28	W
Reverse Working Voltage	$V_{RWM}$	1.0	V
Peak Pulse Current	$I_{PP}$	7	A
Operating Temperature	$T_{OPT}$	-55~+125	°C
Storage Temperature	$T_{stg}$	-55~+150	°C

## 5. Pinning information

Pin	Polarity	Simplified outline	Equivalent Circuit	Marking	Package
2	Bi			DS	DFN1006

## 6. Electrical Characteristics (Tamb=25°C)

Parameter	Symbols	Condition	Min	Typ	Max	Unit
Reverse Working Voltage	$V_{RWM}$				1.0	V
Reverse Breakdown Voltage	$V_{BR}$	$I_T=0.1mA$	2.0			V
Reverse Leakage Current	$I_R$	$V_{RWM}=1.0V$			0.1	$\mu A$
Reverse Holding Current	$V_{Hold}$	$I_{Hold}=50mA$		1.2		V
Clamping Voltage	$V_C$	$I_{pp}=1A, t_p=8/20\mu s$		1.8		V
Clamping Voltage	$V_C$	$I_{pp}=7A, TP=8/20\mu s$		4.0		V
Junction Capacitance	$C_J$	$V_R=0V, f=1MHz$		0.35		pF

## 7. Electrical Parameters

Symbol	Parameter
$I_{PP}$	Maximum Reverse Peak Pulse Current
$V_C$	Clamping Voltage@ $I_{PP}$
$V_{RWM}$	Reverse Working Voltage
$I_R$	Maximum Reverse Leakage Current
$I_{BR}$	Test Current
$V_{BR}$	Breakdown Voltage@ $I_T$
$V_{SB}$	Snapback Voltage
$I_{SB}$	Snapback Test Current
$V_{TRIG}$	Reverse Trigger Voltage
$I_{TRIG}$	Reverse Trigger Current
$V_{HOLD}$	Reverse Holding Voltage
$I_{HOLD}$	Reverse Holding Current

$V_{RWM}$  Reverse stand-off Voltage  
 $I_R$  Reverse leakage current  
 $V_{CL}$  Clamping voltage  
 $I_{PP}$  Peak pulse current

$V_{TRIG}$  Reverse trigger voltage  
 $I_{TRIG}$  Reverse trigger current  
 $V_{BR}$  Reverse breakdown voltage  
 $I_{BR}$  Reverse breakdown current  
 $V_{HOLD}$  Reverse holding voltage  
 $I_{HOLD}$  Reverse holding current

## 8. Typical Characteristics




Figure 1. Peak Pulse Power Rating




Figure 2. Pulse Derating Curve




Figure 3. Typical Clamping Voltage





Figure 4. TLP(1/100nS)

## 9. Outline Drawing



## 10. Reel packing

Package	Reel Size	Reel DIA. (mm)	Q'TY/Reel (pcs)	QTY/Box (pcs)	Q'TY/Carton (pcs)
DFN1006	7'	178	10,000	100,000	400,000

## 11. Important Notice and Disclaimer

Microdiode Semiconductor (Shenzhen) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Microdiode Semiconductor (Shenzhen) makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Microdiode Semiconductor (Shenzhen) assume any liability for application assistance or customer product design. Microdiode Semiconductor (Shenzhen) does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Microdiode Semiconductor (Shenzhen). Microdiode Semiconductor (Shenzhen) products are not authorized for use as critical components in life support devices or systems without express written approval of Microdiode Semiconductor (Shenzhen).