

ME3V3U1BABS

1. Features

- 28Watts peak pulse power ($t_p = 8/20\mu s$)
- Solid-state silicon-avalanche technology
- Capacitance: 0.35pF TYP.
- Low clamping voltage
- Low leakage current
- Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test Air discharge: $\pm 18KV$ Contact discharge: $\pm 16KV$
 - IEC61000-4-4 (EFT) 40A (5/50ns)
 - IEC61000-4-5(Lightning) 7A (8/20us)

2. Application

- USB3.0/3.1/ Type-C
- Thunderbolt interface
- DisplayPort interface
- Handheld portable application

3. Mechanical Data

- Package: DFN1006
- UL Flammability Classification Rating 94V-0
- Packaging: Tape and Reel
- RoHS/WEEE Compliant

4. Absolute Maximum Rating

Parameter	Symbol	Value	Unit
ESD per IEC 61000-4-2 (Contact) ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 16 ± 18	KV
Peak Pulse Power(8/20 μs)	P_{PP}	28	W
Reverse Working Voltage	V_{RWM}	3.3	V
Peak Pulse Current	I_{PP}	7	A
Operating Temperature	T_{OPT}	-55~+125	$^{\circ}C$
Storage Temperature	T_{stg}	-55~+150	$^{\circ}C$

5. Pinning information

Pin	Polarity	Simplified outline	Equivalent Circuit	Marking	Package
2	Bi			0S	DFN1006

6. Electrical Characteristics (Tamb=25°C)

Parameter	Symbols	Condition	Min	Typ	Max	Unit
Reverse Working Voltage	V_{RWM}				3.3	V
Reverse Breakdown Voltage	V_{BR}	$I_T=0.1mA$	5.0			V
Reverse Leakage Current	I_R	$V_{RWM}=3.3V$			0.1	μA
Reverse Holding Current	V_{Hold}	$I_{Hold}=10mA$		1.4		V
Clamping Voltage	V_C	$I_{pp}=1A, t_p=8/20\mu s$		1.8		V
Clamping Voltage	V_C	$I_{pp}=7A, TP=8/20\mu s$		4.0		V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$		0.35		pF

7. Electrical Parameters

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage@ I_{PP}
V_{RWM}	Reverse Working Voltage
I_R	Maximum Reverse Leakage Current
I_{BR}	Test Current
V_{BR}	Breakdown Voltage@ I_T
V_{SB}	Snapback Voltage
I_{SB}	Snapback Test Current
V_{TRIG}	Reverse Trigger Voltage
I_{TRIG}	Reverse Trigger Current
V_{HOLD}	Reverse Holding Voltage
I_{HOLD}	Reverse Holding Current

V_{RWM} Reverse stand-off Voltage
 I_R Reverse leakage current
 V_{CL} Clamping voltage
 I_{PP} Peak pulse current

V_{TRIG} Reverse trigger voltage
 I_{TRIG} Reverse trigger current
 V_{BR} Reverse breakdown voltage
 I_{BR} Reverse breakdown current
 V_{HOLD} Reverse holding voltage
 I_{HOLD} Reverse holding current

8. Typical Characteristics




Figure 1. Peak Pulse Power Rating




Figure 2. Pulse Derating Curve




Figure 3. Typical Clamping Voltage





Figure 4. TLP(1/100nS)

9. Outline Drawing



10. Reel packing

Package	Reel Size	Reel DIA. (mm)	Q'TY/Reel (pcs)	QTY/Box (pcs)	Q'TY/Carton (pcs)
DFN1006	7'	178	10,000	100,000	400,000

11. Important Notice and Disclaimer

Microdiode Semiconductor (Shenzhen) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Microdiode Semiconductor (Shenzhen) makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Microdiode Semiconductor (Shenzhen) assume any liability for application assistance or customer product design. Microdiode Semiconductor (Shenzhen) does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Microdiode Semiconductor (Shenzhen). Microdiode Semiconductor (Shenzhen) products are not authorized for use as critical components in life support devices or systems without express written approval of Microdiode Semiconductor (Shenzhen).